

PHB M 135/3 BBxBB black FR

Article code: RBPH000016

General information

Productgroup	Rubber Belts
Industry segment	Logistics: Distribution & warehousing
Main product feature	Flame retardant
Indication of use	Slider bed, Rollers

Belt construction

Tension layer		polyester/polyamide
Lateral stability		yes, exceptionally laterally stiff
Number of plies		3
Top side	material	impregnated fabric
	color	black
Bottom side	material	impregnated fabric
	color	black

Characteristics

Antistatic (AS)	no	
Flame-retardant (FR)	yes	ASTM D-378

Technical data

Elastic modulus (k1% relaxed)	ISO 21181			12 N/mm	68.52 lbs/in.
Rated working tension				24 N/mm	137.04 lbs/in.
Elongation at rated tension				2 %	
Longitudinal tear				445 N	100.04 Lb
Finished belt gauge				4 mm	0.16 in.
Belt weight				5.5 kg/m ²	1.13 lbs/ft ²
Coefficient of friction	bottom against steel	dynamic		0.2	
		static		0.25	
	top against steel	dynamic		0.2	
		static		0.25	
Operating temperature	continuous	from / to		-20 / 80 °C	-4 / 176 °F
	short	from / to		-20 / 90 °C	-4 / 194 °F
Minimum pulley diameter	flexing			119.4 mm	4.7 in.
Manufacturing width	maximum			1829 mm	72.01 in.

Fabrication

Corrugated side walls	no
Profiles on top side	yes
Profiles on bottom side	yes
Mechanical fasteners	Clipper # 3 HT

Additional information

This sheet contains typical values, which apply to a temperature of approx. 20 °C (68 °F), unless otherwise stated, individual data may differ.

We recommend to pretension the belt to a level that it does not slip at full belt load.

During the life time of the belt, the pretension should not go below this level.

To maximize the service life of the belt we recommend not to increase the belt tension above this level.

Because of continuous development, the presented data is subject to alteration. This data replaces that included in previous publications. Ammeraal Beltech excludes any liability for the incorrect use of the above stated information. Subject to the general terms and conditions of sale and delivery, as applied by its operating companies, are all activities performed and services rendered by Ammeraal Beltech.